

# ELECTRIC TILTING SKILLET



### SPECIFICATIONS:

Shall be a Therma-Tek Model \_\_\_\_\_, electrically heated tilting skillet, c-CSA-us and NSF Certified. The unit shall have a stainless steel cover with spring assist hinges, full width handle, no-drip condensate guide and vent port with swing cover. The pan shall have a sloped front and front hinged for easy tilting pour control and comes complete with a removable pour strainer. Pan is formed from 10 gauge stainless steel with a #4 finish exterior and polished interior with coved corners for ease of cleaning. Cooking surface shall be 5/8" thick stainless steel clad plate ensuring even heat distribution over entire cooking surface. The pan shall be fitted with tubular heating elements clamped to the under side.

The pan shall be mounted on a heavy duty welded frame with stainless steel exterior supported by an all welded 1-5/8" (41mm) stainless steel pipe frame with adjustable bullet feet and rear legs fitted with flange adjustable feet for securing to the floor.

The controls include a thermostat with OFF position and a range of 160-445°F (71-229°C), a thermostat indicator light, pan tilt switch that shuts elements off if tilted more than 5°, and high temperature cut-off set at 536°F(280°C).

Tilting is controlled by an electric motor driven ball drive actuator for smooth and precise tilting action.

Model	kW	Capacity	
TTELTS-30	12	30 gallon	114 litre
TTELTS-40	15	40 gallon	152 litre

### OPERATION SHALL BE BY:

Electric heating elements equipped for operation on:

- 208 VAC, 1 Phase, 50/60 Hz
- 208 VAC, 3 Phase, 50/60 Hz
- 220 VAC, 1 Phase, 50/60 Hz
- 220 VAC, 3 Phase, 50/60 Hz
- 240 VAC, 1 Phase, 50/60 Hz
- 240 VAC, 3 Phase, 50/60 Hz
- 380/220 VAC, 3 Phase, 50/60 Hz.
- 415/240 VAC, 3 Phase, 50/60 Hz.

### STANDARD FEATURES

- ✓ Electric ball drive actuator for smooth and precise tilting action.
- ✓ Stainless steel cover with spring assist hinges, full width handle, no-drip condensate guide and vent port with swing cover.
- ✓ 5/8" clad plate cooking surface with 10 gauge sides.
- ✓ All stainless steel exterior.
- ✓ Pour lip strainer

### OPTIONAL ITEMS AT EXTRA COST:

- 380 VAC, 3 Phase, 50/60 Hz
- 415 VAC, 3 Phase, 50/60 Hz
- 480 VAC, 3 Phase, 50/60 Hz.
- 600 VAC, 3 Phase, 60 Hz.
- 18 kW elements (40 gallon only)
- Etched gallon markings (GMS-30, GMS-40).
- Etched litre markings (LMS-114, LMS-152).
- 2" draw off valve with strainer, side mounted (TVT-2BP).
- 3" draw off valve with strainer, side mounted (TVT-2BP).
- Correctional package

### ACCESSORIES:

- Pan carrier (PC-1).
- Steam pan insert (SPI-30, SPI-40).
- 12" Single pantry faucet with swing spout (SF-12).
- 12" Double pantry faucet with swing spout (DF-12).
- 3" Stainless steel faucet plumbing enclosure (3139-1).
- Single pantry faucet and bracket with 60" pot filler (SF-60).
- Double pantry faucet and bracket with 60" pot filler (DF-60).

## SERVICE CONNECTIONS

- ⚡ – Electrical connection to be as specified on data plate.
- Ⓒ – COLD WATER: 3/8" O.D. tubing to faucet (OPTIONAL)
- Ⓓ – HOT WATER: 3/8" O.D. tubing to faucet (OPTIONAL)

Available kW			AMPS PER LINE								
MODEL	STD.	OPT.	kW	PHASE	208V	220V	240V	380V	415V	480V	600V
TTELTS-30	12	N/A	12	1	57.7	54.5	50.0	N/A	N/A	N/A	N/A
TTELTS-40	15	18		3	33.3	31.5	28.9	18.2	16.7	14.4	11.5
<b>MIN. CLEARANCE</b>			15	1	72.1	68.2	62.5	N/A	N/A	N/A	N/A
SIDES	0			3	41.6	39.4	36.1	22.8	20.9	18.0	14.4
<b>BACK</b>			18	1	86.5	81.8	75.0	N/A	N/A	N/A	N/A
BACK		6 [152]		3	50.0	47.2	43.3	27.3	25.0	21.7	17.3

## DIMENSIONS

MODEL	SHIPPING WT.	CAPACITY	UNITS	A	B	C	D	E	F		G	
TTELTS30	490 lbs. [222 kg]	30 ca ons 114 litres	inches mm	36.0 914	33.5 851	7 1880	33.5 851	23.50 597	ø2 3.6	ø3 5.5	ø2 7.3	ø3 13.1
TTELTS40	675 lbs. [306 kg]	40 gallons 152 litres	inches mm	48.0 1219	45.5 1156	74 1880	43.5 1105	23.0 584	ø2 92	ø3 140	ø2 186	ø3 333

